

TEXMO



أداء يمكنك الوثوق
PERFORMANCE YOU CAN TRUST



TEXMO Automatic Pump Controller

TAPC - 1



Rated voltage	220V - 240V, 110V - 120V, 110V - 240V
Frequency	50/60 Hz
Max. current	10A, 20A, 30A
Max. power	1.1KW 1.5KW 2.2KW
Starting pressure setting	1.2bar 1.5bar 2.2bar
Max. working pressure	10 bar
Connection thread	R1"
Protection rating	Ip65
Max. working temperature	60°C
Wiring requirement	7.5 - 9mm

TAPC - 3A



Rated voltage	220V - 240V 110V - 120V
Frequency	50/60Hz
Max. current	10A, 20A, 30A
Max. power	1.1KW 1.5KW 2.2KW
Starting pressure setting	1.5 bar 2.2 bar 3.5 Bar
Max. working pressure	10 bar
Connection thread	Inlet male thread G1" Outlet female threads G1"
Protection rating	Ip65
Max. working temperature	60°C
Wiring requirement	7.5-9mm

TFS- 5



Rated voltage	220V - 240V 110V - 120V
Frequency	50/60Hz
Max. current	10A, 20A, 30A
Connection thread	R1"
Protection rating	Ip68
Max. working temperature	55°C
Wiring requirement	7.5-9mm



TEXMO

MARKETING BY : MAJESTIC PRIDE INDUSTRY
INDIA - U.A.E - OMAN
www.mpgtc.com, E-mail : sales@mpgtc.com

TEXMO

FINOLEX

MAJESTIC