

TEXMO



أداء يمكنك الوثوق
PERFORMANCE YOU CAN TRUST

Texmo Open Well Submersible Pump Stainless Steel 304

Applications

- For water supply from open wells, tanks or reservoirs.
- For domestic use, Civil and industrial applications.
- For garden and irrigation, Utilization of rain water

Function and feature

- Single phase with built-in capacitor and thermal protector on control box required Three phase with built-in thermal protector
- Hermetically sealed motor equip built-in thermal protection. The protector in the motor can automatically cut off the power when it overheats or over current.
- Close coupled multi-stage submersible pump in chrome -nickel stainless steel.
- Hydraulic part under the motor and motor cooled by the pumped water for safe operation also with the pump only partially immersed
- Double shaft seal with interposed oil chamber
- The suction strainer prevents the entrance of solids with diameter bigger than 2 mm.

Specification

- Water temperature : up to 35°C
- Minimum internal diameter of well: Ø132mm.
- Power Supply : single phase 220V $\pm 10\%$, Three phase 400V $\pm 10\%$, 50 Hz
- Power : 0.75 to 1.5Kw
- Insulation Class: F
- Protection Class : IP 68
- Capacity : up to 133 LPM
- Head : up to 88m
- Minimum immersion depth: 100mm.
- Maximum immersion depth : 20m suitable (with cable length)
- PH : 6.5 to 8.5
- Cable Length 40mtr.



Model	Power		Outlet Inch	H	N.W (Kg)	Cable (mtr)	Q	US GPM	0	4	7	9	11	13	15	18	20	-
	KW	HP						M ³ /H	0	1	1.5	2	2.5	3	3.5	4	4.5	-
T005	0.75	1		545	14.9	30		LPM	0	17	25	33	42	50	58	67	75	-
T007	1.1	1.5	1 1/4"	640	18	40	H meters		53	49.5	47	44	40	35	30	25	19	-
									88	81	77.0	71.3	66	60	52.5	46	37	-

Model	Power		Outlet Inch	H	N.W (Kg)	Cable (mtr)	Q	US GPM	0	11	13	15	18	20	22	25	31	35
	KW	HP						M ³ /H	0	2.5	3	3.5	4	4.5	5	5	7	8
T006	1.1	1.5	1 1/4"	590	17	40		LPM	0	42	50	58	67	75	83	100	117	133
							H meters		88	60	58	56	54	51.5	49	42	34	20.5
T008	1.5	2	2		25.9	40	H meters		90	86	83	75	68	65	58	54	48	20.5

MODEL	Power		Voltage	Height	Q	m ³ /h	0	3	6	9	10	12	15	18	21
	KW	HP				L/min	0	50	100	150	167	200	250	300	350
T1003	2.2	3	220v	639mm	H meters		49	46	43	39	38	35	30	24	15



TEXMO

MARKETING BY : MAJESTIC PRIDE INDUSTRY
INDIA - U.A.E - OMAN
www.mpgtc.com, E-mail : sales@mpgtc.com

TEXMO

FINOLEX

MAJESTIC